



Silopren* LSR 2530

Silopren© LSR 2530

Description

Silopren LSR 2530 is a two-component liquid silicone rubber especially developed for the coating of textiles and glassfibre fabrics.

Key Features and Benefits

Vulcanisates consisting of **Silopren LSR 2530** are distinguished by the following properties:

- low viscosity
- excellent thermal stability
- high stability and flexibility at low temperatures
- good rubber-like properties
- long service life at dynamic stress
- high stability to ozone and ultraviolet light
- outstanding resistance to ageing
- excellent dielectric behaviour over a wide range of temperatures
- not readily combustible, does not melt or drip
- easy pigmentable with the LSR Colour Pastes

Typical Physical Properties

Typical properties of the rubber:			
		A-part	B-part
Appearance		translucent	translucent
Viscosity in Pa.s $\gamma = 10 \text{ s}^{-1}$ at 20 ° C	DIN 53018	60	60
The pot-life of the mixture of the two components (closed vessel) at 20 ° C is three days. Increased temperatures reduce the pot-life. Typical properties of the vulcanisate:			
Mixing ratio of components A : B = 1 : 1.			
Vulcanisation : 10 min. 175°C			
Density	DIN 53 479 A	g/cm ³	1.05
Shore A hardness	DIN 53 505		30
Tensile strength	DIN 53 504 S2	N/mm ²	4.0
Elongation at break	DIN 53 504 S2	%	500
Tear strength	ASTM D 624 die B	N/mm	10

Potential Applications

Because of the outstanding properties **Silopren LSR 2530** is particularly suitable for the following applications: textile coating for protective suits or conveyor belts, coating of glassfibre fabric sleeves, coating of fabrics for compensators, tents and other technical applications s.o.

Processing Recommendations

Ready-to-use mixtures (of the components A and B) are fed directly to the coating machine from the original containers by means of a metering and mixing unit. The mixture, consisting of the two components in the ratio 1:1, is applied by means of knives or cross heads as requested thickness onto the fabrics. The coated fabrics must be cured in the heating channel at temperatures of 150 - 180 ° C. The addition-crosslinking silicone rubber vulcanises free of dissociation products within a few seconds.

Containers

Silopren LSR 2530 is available in 20 kg pails and 200 kg drums.

Approvals

Meets flame retardant class UL 94 HB

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

The individual components of **Silopren LSR 2530** have a warranty period of 6 months from the date of shipment, if stored in the original unopened containers at room temperature (max. 27 ° C). Containers, which have been opened, must be kept tightly closed afterwards.

Customers should review the latest Material Safety Data Sheet (MSDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, and any special storage conditions required for safety. MSDS are available at www.momentive.com or, upon request, from any Momentive Performance Materials (MPM) representative. **For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center.** Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

From automotive to healthcare, from electronics to construction, products from Momentive Performance Materials Inc. are practically everywhere you look. We are a global leader in silicones and advanced materials with a 70+ year heritage of innovation and being first to market – with performance applications that improve everyday life. By knowing our customers' needs and creating custom technology platforms for them, we provide science based solutions to help customers increase performance, solve product development issues and engineer better manufacturing processes.

Contact Information

For product prices, availability, or order placement, contact our customer service by visiting www.momentive.com/Contacts

For literature and technical assistance, visit our website at: www.momentive.com

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.

***Silopren is a trademark of Momentive Performance Materials Inc.**

DISCLAIMER

The information provided herein was believed by Momentive Performance Materials Inc. (collectively with its subsidiaries, "Momentive") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product, and to determine the suitability of the product for user's intended application or use. All products supplied by Momentive are subject to Momentive's standard terms and conditions of sale. **MOMENTIVE MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY MOMENTIVE**, except that the product shall conform to Momentive's specifications. Nothing contained herein constitutes an offer for the sale of any products.