



Dielectric Silicone Gel Potting Materials



Momentive Performance Materials provides leading-edge silicone technologies to help meet performance and productivity challenges in a wide range of automotive and electronic applications.

Momentive's dielectric silicone gel materials are extremely soft, lightly cross linked silicone polymers that provide good stress relief and self healing properties while maintaining dimensional stability and provide a tacky adhesion. These properties make the dielectric gels excellent candidates to consider for protection of fragile electronic components from moisture and the contaminants. Momentive offers a range of room temperature cure gels including one and two part products, and specialized grades that can help provide improved vibration dampening, very fast RT cure and UV activated cure.

Key Features

- Temperature resistance
- Low modulus, good dampening properties
- Low viscosity
- Tacky adhesion at RT
- High dielectric strength (> 18 kV/mm)

Typical Benefits

- Under the hood usage
- Thermal and mechanical stress protection
- Easily flow around components
- Prevent formation of thermally induced voids
- Reliability

Potential Applications

- Sensor potting
- ECU potting
- Power module potting
- Cable joints

Typical Physical Properties

(selected grades only; please contact us for material selection support)

Product	System (1)	Ratio (w/w)	Cure Time	Work life (@ RT)	Penetration (2) (1/10 mm)	Viscosity (Pa·s)	Feature
TSE3051	AC, 1K	n.a.	1 h at 150°C	-	85	0.7	1 Part - Easy handling
TSE3070	AC, 2K	1:1	0.5 h at 70°C	4 hr	65	0.8	Excellent vibration damping - high elongation
TSE3062	AC, 2K	1:1	0.5 h at 70°C	1 hr	55	1	Excellent temperature stability
Silopren* Gel 6209FC	AC, 2K	1:1	1 h at 100°C	0.5 hr	85	1	Excellent vibration damping
Silopren Gel 7212	AC, 2K	1:1	1 h at 100°C	0.75 hr	120	1.5	Very soft gel
Silopren Gel 7206	AC, 2K	1:1	20 minutes at 23°C	10 minutes	70	0.15	Low viscosity, very fast RT cure

(1) AC = Addition Cure, UV = UV activated Addition Cure

(2) Penetration in 1/10 of a mm - measured with quarter cone

(3) CT = Cure Time, TFT = Tack Free Time

Typical properties are average data and are not to be used as or to develop specifications.

*Silopren is a trademark of Momentive Performance Materials Inc.



www.momentive.com

260 Hudson River Road,
Waterford, NY 12188 USA

+1 800 295 2392

+1 614 986 2495

For more information and sampling inquiries, please visit momentive.com/CustomerService

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.
Copyright 2017, Momentive Performance Materials Inc. All rights reserved.